

Lindemann musicbook: SOURCE CD II

Art.Nr.: mbSOURCECD2 / manufacturer: [Lindemann Audiotechnik](#)

3.890,00EUR

incl. 19% VAT incl. Shipping

 Goods can be ordered - please inquire about the delivery time (not in stock)



The Musicbook SOURCE CD II is a versatile signal source that meets even the highest demands on sound quality. Be it music from streaming services or from a music server, from CDs or LPs, everything's possible and easy to operate via the app. Friends of high-class headphones will also get their money's worth: the integrated headphone amplifier defines new standards in this class. The icing on the cake is the excellent phono MM input for turntables!

Product information



Connect your Musicbook SOURCE to a suitable power amplifier such as the Musicbook POWER or directly to active loudspeakers, and from now on you'll be enjoying music in the most beautiful way.

Technical Specifications:

Measurement conditions:

22 °C, 230 V mains voltage, Audio Precision AP2722

Mains connection: 90 – 240 V, 50 – 60 Hz

Power consumption: 0.2 W stand-by, 8 W operation, 18 W max.

Dimensions (W x H x D): 280 x 220 x 63 mm (11 x 8.7 x 2.5 in.)

Weight: 2.6 kg (5.73 lbs)

D/A converter:

Resolution: 768 kHz/32 bit and DSD 512

Dynamic range: >125 dB

THD & Noise: 60 dB

Converter architecture: two AK4493 DACs in dual differential mono mode, AK4137 re-sampler

Output voltage: 3 V @ 0 dBFS RCA, 6 V @ 0 dBFS XLR

Network player:

Ethernet: 100 Mbit/s

WLAN: Dual-band 802.11a/b/g/n/ac, WPS support

Bluetooth: 4.2, A2DP

USB: High-speed host interface for harddisks, USB sticks, DVD ROM drives, max. output current 1.5 A

Supported codecs: WAV, FLAC, AIFF, ALAC, MP3, AAC,

Ogg Vorbis, WMA, DSD

UPnP and DLNA support

PCM resolution: 44.1 kHz up to 384 kHz, 24bit (WLAN up to 192 kHz)

DSD resolution: DSD 64 up to DSD 256 (WLAN up to DSD 128)

Gapless playback

Streaming services: TIDAL Connect, Qobuz, Deezer, HighResAudio, Spotify Connect

Internet radio and podcast

Roon Ready

Analog preamp:

Inputs: two analog line inputs with 50 kOhms of input impedance.

Max. input voltage 3 V unbalanced. MM input for connecting a turntable. Connection values MM: 47 kOhms / 150 pF.

Outputs: one balanced and one unbalanced output. The outputs may be used independently. Output impedance: RCA: 100 ohms, XLR: 100 Ohms. Max. output voltage: 3 V unbalanced, 6 V balanced

Volume level control range: 0 to 80 dB in 1 dB steps

Balance control: + / - 6 dB in 1 dB steps

Frequency response: 2 – 200 kHz (-3 dB)

THD & Noise: < 0.001 % @ 3 V output

Headphone amplifier:

Headphone connector: 6.35 mm (1/4") jack socket

Headphone gain: 0 dB / 12 dB switchable

Recommended headphone impedance: 16 - 200 ohms

Product information



Damping factor of headphone output: >100