Product information

Lindemann musicbook: POWER 1000 II

Art.Nr.: mbPOWER1000II / manufacturer: Lindemann Audiotechnik







3.590,00EUR

incl. 19% VAT incl. Shipping

Delivery time: 1 - 3 working days within Germany. Only a few in stock!

1 in stock

Technical Specifications:

General:
Power supply: 90-240V, 50-60Hz
Power consumption: 0.5W standby, 26W operation, 1200W max.
Dimensions (W x H x D): 280 x 220 x 63 mm

Product information

Weight: 3.4kg

Power amplifier:
XLR inputs: balanced, analog line-level inputs
Input voltage for full modulation: 2.38 V
Input impedance: 20 kOhm
Speaker outputs: banana plug (4 mm)
Speaker impedance range: 4 – 8 ohms
Output power: 2 x 500 W at 4 ohms
Gain: 26dB
THD: 110dB

Automatic switching on:
Switch-on threshold: approx. 0.2 mV symmetrical
Switch-on delay: approx. 2-3 seconds
Switch-off time: approx. 60 minutes

Protection circuits:
DC at output: Amplifier switches off. The display lights up permanently red. The device must be unplugged for 10 seconds and restarted.
Overtemperature: Amplifier flashes red. Cause: Overload, insufficient convection cooling, room temperature too high. If the temperature continues to rise, the amplifier will be switched off until the device has cooled down.
Current limitation: Amplifier switches off the signal. Switching threshold output current: 27 A.