

Lindemann musicbook: POWER 1000 II

Art.Nr.: mbPOWER1000II / manufacturer: [Lindemann Audiotechnik](#)

3.590,00EUR

incl. 19% VAT incl. Shipping

 Delivery time: 1 - 3 working days within Germany. Only a few in stock!

1 in stock



Technical Specifications:

General:

Power supply: 90-240V, 50-60Hz

Power consumption: 0.5W standby, 26W operation, 1200W max.

Dimensions (W x H x D): 280 x 220 x 63 mm

Product information



Weight: 3.4kg

Power amplifier:

XLR inputs: balanced, analog line-level inputs

Input voltage for full modulation: 2.38 V

Input impedance: 20 kOhm

Speaker outputs: banana plug (4 mm)

Speaker impedance range: 4 – 8 ohms

Output power: 2 x 500 W at 4 ohms

Gain: 26dB

THD: 110dB

Automatic switching on:

Switch-on threshold: approx. 0.2 mV symmetrical

Switch-on delay: approx. 2-3 seconds

Switch-off time: approx. 60 minutes

Protection circuits:

DC at output: Amplifier switches off. The display lights up permanently red. The device must be unplugged for 10 seconds and restarted.

Overtemperature: Amplifier flashes red. Cause: Overload, insufficient convection cooling, room temperature too high. If the temperature continues to rise, the amplifier will be switched off until the device has cooled down.

Current limitation: Amplifier switches off the signal. Switching threshold output current: 27 A.
