

Lindemann music book: COMBO

Art.Nr.: MBC220005 / manufacturer: [Lindemann Audiotechnik](#)

3.890,00EUR

incl. 19% VAT incl. Shipping

 Goods can be ordered - please inquire about the delivery time (not in stock)



The first all-in-one music player from LINDEMANN. The logical continuation of the extremely successful Musicbook series. Fully equipped, with a unique design and truly audiophile genes!

The Musicbook COMBO joins the proven streaming platform of the Musicbook SOURCE and the power amp technology of the Musicbook POWER. A multitude of features and connectivity options make your tonal dreams come true. Simply connect the

matching speakers - and you're set to enjoy music in its most beautiful form. Rich in detail and yet relaxed, with a large stage or a small ensemble, with vigorous dynamics or soft and soulful.

No matter whether from streaming services or from a music server, from CDs or LPs, almost every playback is possible and conveniently operable via the app. Also the friends of high-quality headphones get their full money's worth: the built-in headphone amp sets benchmarks in this class. And the icing on the cake is the excellent phono MM input for turntables!

Technical Specifications:

Measurement conditions:

22 °C, 230 V mains voltage,

Audio Precision AP2722

Mains connection: 90 – 240 V, 50 – 60 Hz

Power consumption: 0.5 W stand-by, 16 W operation, 160 W max. Dimensions (W x H x D): 280 x 220 x 63 mm (11 x 8.7 x 2.5 in.)

Weight: 3 kg (6.61 lbs)

D/A converter:

Resolution: 768 kHz/32 bit and DSD 512

Dynamic range: >125 dB

THD & Noise: 60 dB

Converter architecture: two AK4493 DACs in dual differential mono mode, AK4137 re-sampler

Network player:

Ethernet: 100 Mbit/s

WLAN: Dual-band 802.11a/b/g/n/ac, WPS support

Bluetooth: 4.2, A2DP

USB: High-speed host interface for harddisks, USB sticks,

CD ROM drives, max. output current 1.5 A

Supported codecs: WAV, FLAC, AIFF, ALAC, MP3, AAC, Ogg Vorbis, WMA, DSD

UPnP and DLNA support

PCM resolution: 44.1 kHz up to 384 kHz, 24bit (WLAN up to 192 kHz)

DSD resolution: DSD 64 up to DSD 256 (WLAN up to DSD 128) Gapless playback

Streaming services: TIDAL Connect, Qobuz, Deezer, HighResAudio, Spotify Connect

Internet radio and podcast

room ready

Analog Preamp:

Inputs: two analog line inputs (RCA) with 50 kOhms of input impedance. Max. input voltage 2.5 V. MM input for connecting a turntable.

Connection values MM: 47 kOhms / 150 pF / 40 dB gain.

Output: line level output (RCA). Output impedance: 100 ohms. Max. output voltage: 1 V.

Volume level control range: 0 to 80 dB in 1 dB steps Balance control: + / - 6 dB in 1 dB steps

Frequency response: 2 – 200 kHz (-3 dB)

THD & Noise: < 0,001 % @ 3 V output

Power amplifier:

Poweroutput: 2 x 130 W @ 4 ohms, 2 x 70 W @ 8 ohms.

THD&Noise: < 0.03 % @ 10 W into 4 ohms

Product information



Dampening factor: > 500.

Headphone amp:

Headphone connector: 6.35 mm (1/4") jack socket

Headphone gain: 0 dB / 12 dB switchable

Recommended headphone impedance: 16 - 200 ohms

Damping factor of headphone output: >100